Specification	Value
Printheads	1
Inks	Dye Based
Maximum Lines of Print	5
Maximum Line Speed (1)	279 m/min (914 ft/min)
Environmental Protection	IP55 (IP65 optional)
Core Life (Maintenance Interval)	Up to 12,000 hours
Umbilical Length	3 m (9.8 ft) optional 6 m (19.6 ft)
Message Storage Capability	100
Smart Cartridge™	Included
Plug and Play Printhead Modules	Included
USB	Included
Communications	Ethernet and RS-232 Serial
Positive Air	Included
Expanded I/O Ports and Control	#
Display (User Interface)	LCD with membrane keyboard

Optional

(1) Based upon single line, 10 characters per inch

Q1: طابعة □□□□□□□ □□□□□□□ □□□□□ □□□□□□ □□□□□

Q2: □□□□□□□□□ □□□□□ □□□□□ □□□□□

Q3: □□□□□□□□□ □□□□ □□ □□□□□□ الطابعة الخاصة بك يكون

Q4: □□□□□□□ □□□ □□ □□□ □□

Q6.

□□□□□□ □□□□□□□**:** (sales@cheef.cn) ، WeChat / Whatsapp / Tel: + 86-181-6857-5767 □□□ □□□□ □□ □□□□ □□ □□□□□□□□□□