

Specification	6530
Printer Mode	Intermittent and Continuous Motion
Print Gap	Consistent 0.020" (0.5mm)
Ribbon Widths	6530(53mm) :0.8" (20mm), 2.2" (55mm) max 6530(107mm) :2.2" (55mm),4.33" (110mm) max
Bar Code Printing	EAN 8, EAN 13, UPC-A, UPC-E, Code 39, EAN 128, Code 128, ITF, RSS (including 2D composite codes); others may be available upon request
Operator Interface	TFT SVGA 800x480 full-color LCD and touch screen, WYSIWYG print preview, full on-board diagnostics, 3 levels of password protection, extensive language support
Leader/Follower Capability (Up to 4 Printers Controlled by One User Interface)	Up to four Videojet DataFlex® 6530 printers controlled via a single CLARiTY™ control unit
Standard Communication	RS232, dual Ethernet, USB memory stick and scanner support, Binary and ASCII comms protocols, Windows™ drivers ZPL and SATO emulations
Web Browser Capability	Yes
Continuous Mode:	–
Maximum Print Area (Width x Length)	6530(53mm) :2.1" (53mm) wide x 7.9" (300mm) long 6530(107mm) :4.3" (107mm) wide x 11.8" (300mm) long
Maximum Print Speed	39.4 in./sec (1,000mm/sec)
Minimum Print Speed	0.04 in./sec (1mm/sec)
Estimated Maximum Throughput (Single Line Code)	6530(53mm) :Up to 700 prints per minute 6530(107mm) : Up to 450 prints per minute
Intermittent Mode:	–
Maximum Print Area (Width x Length)	6530(53mm) : 2.1" (53mm) wide x 2.95" (75mm) long 6530(107mm) : 4.3" (107mm) wide x 2.95" (75mm) long
Maximum Print Speed	6530(53mm) : 31.5 in./sec (800mm/sec) 6530(107mm) : 23.6in./sec (600mm/sec)
Minimum Print Speed	0.4 in./sec (10mm/sec)

