

Specification	Value
Label Application Method	Direct Apply (standard) Other optional applicators: Telescopic tamp, Front of Pack, Rear of Corner Wrap
Print Technology	Thermal Transfer printing with Intelligent Motion™ Ribbon Drive or Direct Thermal Printing with 2" (53mm), 4" (107mm) and 6" (160mm) printhead versions
Ribbon Width	Minimum 2.2" (55mm), 3.0" (76mm), 4.3" (110mm) (standard) and 6.4" (162mm) / Up to 830m
Print Resolution	300dpi (200dpi in emulation mode)
Print Speed/ Throughput	<4" label width up to 500mm/sec in standard mode and up to 750mm/sec in high speed mode >4" label width up to 400mm/sec in standard mode up to 150 packs/minute with a 4"x6" label dependent on label size and application
Emulations	ZPL, SBPL
Label Width/Length/Capacity	1.6" to 6.5" / 2.0" to 12.9" (40mm to 165mm / 50mm to 330mm) spool diameter
Interface	CLARiTY Controller – A single intuitive screen with on-board label database and video tutorials
Connectivity	Ethernet, RS232, Configurable I/O (24V, PNP and volt free) and USB
Certification	CE and TÜV

CHEEF INKJET PRINTER INK MANUFACTURER

