

| | |
|--------------------------------------|---|
| Specification [↵] | Controller: 210135°37mm(HWD)/8.3°5.3°1.46inch [↵] Print head: 126 100"31mm(HWD)/4.9"3.9"1.2 inch [↵] |
| Language [↵] | Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian [↵] |
| Resolution [↵] | 50-600DPI [↵] |
| Counters [↵] | Series No, Carton No, Pallet No etc [↵] |
| Printable heights(mm) [↵] | 1-76.2mm (max 6 heads), if it is one head, the height is 12mm. [↵] |
| Printing speed [↵] | 0-60 m/min(300DPI) 0-30 m/min(600 DPI) [↵] |
| Production speed [↵] | Production speed can be set as request, automatic calculation and external synchronizer [↵] |
| Barcode [↵] | UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR [↵] |
| Date format [↵] | Production date, expiry date with several formats for option [↵] |
| Database support [↵] | PC software supports MS Excel, MS Access, SQL2000, SQL2005 SQL2008 etc. database formats [↵] |
| Database Source Support [↵] | Provide standard rs-232, Ethernet port, simplify the integration for customers [↵] |
| Interface [↵] | 1)7 inch 800*480 resolution color LCD touch screen [↵] 2)Display screen using new touch operation interface, easy to learn and use [↵] 3)Printer can work separately without PC software [↵] |
| Port [↵] | 1)Ethernet: 100mb/S, synchronized control of multiple devices via PC [↵] 2)USB2.0 Port: Support u-disk [↵] 3)DB15: For external devices like photocell, synchronizer or alarm kit connection [↵] |
| Ink management [↵] | Identify ink type automatically and recommend the best printing parameter [↵] Original authentic HP ink cartridge guaranteed [↵] Automatic measuring system for ink consumption [↵] |
| Installation [↵] | Standard side printing bracket, down printing bracket and anti-shock, users can install according to their needs, spring mechanism is optional [↵] |
| Power supply [↵] | AC 100v-240v 50-60hz, 90W(Specified AC adaptor) [↵] |
| Certificate [↵] | CE、FCC [↵] |