

<b>Product Name</b>	Linx inkjet printer 4900
<b>Average power</b>	200W
<b>Printing Lines</b>	1-2lines
<b>Print head</b>	2 m, 4 m long nozzle conduit optional
<b>Print speed (maximum)</b>	7m / s
<b>Character height</b>	2.1 mm ~8.8mm
<b>Font type</b>	5 x 5, 7 x 5, 9 x 6, 16 x 11, 24 x 17 dot matrix font
<b>Weight</b>	24kg
<b>Voltage</b>	115 ~ 230 V
<b>Frequency</b>	50Hz-60Hz
<b>Power</b>	200W
<b>Operating temperature</b>	5 ~ 45 °C
<b>Relative humidity</b>	Large relative humidity, no condensation 90%
<b>Protection standards</b>	IP55

**Performance:**

spray printing line number 1 ~ 2, character height 2.1 mm ~ 8.8 mm, high speed 7 m / s

Font type 5 \* 5, 7 \* 5, 9 \* 6, 16 \* 11, 24 \* 17 dot matrix font

**Features:**

1. Single button start and close; 2. Standard QWERTY keyboard; 3. It can store 50 pieces of data
4. Nozzle automatic cleaning function 5. Automatic power off 6. Multiple operating languages
7. With password protection function 8. Dynamic data and pattern storage capacity
9. In case of sudden power failure, the nozzle will close automatically

**Programming and jet printing performance :**

1. Spray printing can make and edit data at the same time.
2. The height, width and delay of jet printing can be adjusted
3. Fixed or variable text
4. Pattern editor
5. Real time function, timing data function, automatic date calculation function
6. Multiple shift and date formats, flexible date options
7. Automatic counting function, continuous printing function

**Nozzle:**

2 m, 4 m long nozzle pipe optional, positive pressure air option, oblique nozzle cover, for "roof type" beverage packaging drinking

**Ink:**

1. Ordinary ink 2, environmental friendly ink 3. Food grade ink, a variety of colors can be selected. 4. Pigment based ink, a variety of colors can be selected

**Interface / communication interface:**

1. RS232 2, synchronizer 3, main / auxiliary product detection

**Structural features:**

Base and housing stainless steel



CHEEF INKJET PRINTER INK MANUFACTURER