

Specification <sup>Ⓟ</sup>	Controller: 210135°37mm(HWD)/8.3°5.3°1.46inch <sup>Ⓟ</sup> Print head: 126 100"31mm(HWD)/4.9"3.9"1.2 inch <sup>Ⓟ</sup>
Language <sup>Ⓟ</sup>	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian <sup>Ⓟ</sup>
Resolution <sup>Ⓟ</sup>	50-600DPI <sup>Ⓟ</sup>
Counters <sup>Ⓟ</sup>	Series No, Carton No, Pallet No etc <sup>Ⓟ</sup>
Printable heights(mm) <sup>Ⓟ</sup>	1-76.2mm <sup>Ⓟ</sup>
Printing speed <sup>Ⓟ</sup>	0-60 m/min(300DPI) 0-30 m/min(600 DPI) <sup>Ⓟ</sup>
Production speed <sup>Ⓟ</sup>	Production speed can be set as request, automatic calculation and external synchronizer <sup>Ⓟ</sup>
Barcode <sup>Ⓟ</sup>	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR <sup>Ⓟ</sup>
Date format <sup>Ⓟ</sup>	Production date, expiry date with several formats for option <sup>Ⓟ</sup>
Database support <sup>Ⓟ</sup>	PC software supports MS Excel, MS Access, SQL2000, SQL2005 SQL2008 etc. database formats <sup>Ⓟ</sup>
Database Source Support <sup>Ⓟ</sup>	Provide standard rs-232, Ethernet port, simplify the integration for customers <sup>Ⓟ</sup>
Interface <sup>Ⓟ</sup>	1)7 inch 800*480 resolution color LCD touch screen <sup>Ⓟ</sup> 2)Display screen using new touch operation interface, easy to learn and use <sup>Ⓟ</sup> 3)Printer can work separately without PC software <sup>Ⓟ</sup>
Port <sup>Ⓟ</sup>	1)Ethernet: 100mb/S, synchronized control of multiple devices via PC <sup>Ⓟ</sup> 2)USB2.0 Port: Support u-disk <sup>Ⓟ</sup> 3)DB15: For external devices like photocell, synchronizer or alarm kit connection <sup>Ⓟ</sup>
Ink management <sup>Ⓟ</sup>	Identify ink type automatically and recommend the best printing parameter <sup>Ⓟ</sup> Original authentic HP ink cartridge guaranteed <sup>Ⓟ</sup> Automatic measuring system for ink consumption <sup>Ⓟ</sup>
Installation <sup>Ⓟ</sup>	Standard side printing bracket, down printing bracket and anti-shock, users can install according to their needs, spring mechanism is optional <sup>Ⓟ</sup>
Power supply <sup>Ⓟ</sup>	AC 100v-240v 50-60hz, 90W(Specified AC adaptor) <sup>Ⓟ</sup>
Certificate <sup>Ⓟ</sup>	CE、FCC <sup>Ⓟ</sup>