

Specification [Ⓟ]	Controller: 210135°37mm(HWD)/8.3°5.3°1.46inch [Ⓟ] Print head: 126 100°31mm(HWD)/4.9°3.9°1.2 inch [Ⓟ]
Language [Ⓟ]	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian [Ⓟ]
Resolution [Ⓟ]	50-600DPI [Ⓟ]
Counters [Ⓟ]	Series No, Carton No, Pallet No etc [Ⓟ]
Printable heights(mm) [Ⓟ]	1-76.2mm [Ⓟ]
Printing speed [Ⓟ]	0-60 m/min(300DPI) 0-30 m/min(600 DPI) [Ⓟ]
Production speed [Ⓟ]	Production speed can be set as request, automatic calculation and external synchronizer [Ⓟ]
Barcode [Ⓟ]	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR [Ⓟ]
Date format [Ⓟ]	Production date, expiry date with several formats for option [Ⓟ]
Database support [Ⓟ]	PC software supports MS Excel, MS Access, SQL2000, SQL2005 SQL2008 etc. database formats [Ⓟ]
Database Source Support [Ⓟ]	Provide standard rs-232, Ethernet port, simplify the integration for customers [Ⓟ]
Interface [Ⓟ]	1)7 inch 800*480 resolution color LCD touch screen [Ⓟ] 2)Display screen using new touch operation interface, easy to learn and use [Ⓟ] 3)Printer can work separately without PC software [Ⓟ]
Port [Ⓟ]	1)Ethernet: 100mb/S, synchronized control of multiple devices via PC [Ⓟ] 2)USB2.0 Port: Support u-disk [Ⓟ] 3)DB15: For external devices like photocell, synchronizer or alarm kit connection [Ⓟ]
Ink management [Ⓟ]	Identify ink type automatically and recommend the best printing parameter [Ⓟ] Original authentic HP ink cartridge guaranteed [Ⓟ] Automatic measuring system for ink consumption [Ⓟ]
Installation [Ⓟ]	Standard side printing bracket, down printing bracket and anti-shock, users can install according to their needs, spring mechanism is optional [Ⓟ]
Power supply [Ⓟ]	AC 100v-240v 50-60hz, 90W(Specified AC adaptor) [Ⓟ]
Certificate [Ⓟ]	CE、FCC [Ⓟ]