

Specification↵	Controller: 210135°37mm(HWD)/8.3°5.3°1.46inch↵ Print head: 126 100"31mm(HWD)/4.9"3.9"1.2 inch↵
Language↵	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian↵
Resolution↵	50-600DPI↵
Counters↵	Series No, Carton No, Pallet No etc↵
Printable heights(mm)↵	1-76.2mm (max 6 heads), if it is one head, the height is 12mm.↵
Printing speed↵	0-60 m/min(300DPI) 0-30 m/min(600 DPI)↵
Production speed↵	Production speed can be set as request, automatic calculation and external synchronizer↵
Barcode↵	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR↵
Date format↵	Production date, expiry date with several formats for option↵
Database support↵	PC software supports MS Excel, MS Access, SQL2000, SQL2005 SQL2008 etc. database formats↵
Database Source Support↵	Provide standard rs-232, Ethernet port, simplify the integration for customers↵
Interface↵	1)7 inch 800*480 resolution color LCD touch screen↵ 2)Display screen using new touch operation interface, easy to learn and use↵ 3)Printer can work separately without PC software↵
Port↵	1)Ethernet: 100mb/S, synchronized control of multiple devices via PC↵ 2)USB2.0 Port: Support u-disk↵ 3)DB15: For external devices like photocell, synchronizer or alarm kit connection↵
Ink management↵	Identify ink type automatically and recommend the best printing parameter↵ Original authentic HP ink cartridge guaranteed↵ Automatic measuring system for ink consumption↵
Installation↵	Standard side printing bracket, down printing bracket and anti-shock, users can install according to their needs, spring mechanism is optional↵
Power supply↵	AC 100v-240v 50-60hz, 90W(Specified AC adaptor)↵
Certificate↵	CE、FCC↵