

| | |
|------------------------------|-----------------------|
| Product Name | Inkjet printer 1510 |
| Average power | 120W |
| Printing Lines | 1-5lines (2mm-10mm) |
| Print head size | 43.1mm*240.5mm |
| Print speed (maximum) | 278.6m/min (one line) |
| Catheter length | 3m or 6m |
| Machine size | 541mm*345mm*285mm |
| Weight | 18KG |
| Voltage | 100-120/200-240VAC |
| Frequency | 50Hz-60Hz |
| Power | 120W |
| Operating temperature | 5-45°C |
| Relative humidity | 0-90%,Non-frosting |
| Data interface | RS-232 |

Keyboard: A clad keyboard with haptic feedback, including 72 numeric keys, letter keys, and special function keys. Standard computer keyboard, close to international PC practice.

Display: 320 x 240 bright blue backlight 5.7" LCD display.

The You See By-You-Go screen displays information editing.

Customer identification/pattern: User identification/pattern can be edited directly on the code press or computer.

Character settings: Chinese, Russian/Bulgarian, Turkish/Scandinavian, Greek, Arabic, Japanese/Japanese, Hebrew, Korean Chinese, Eastern European and European/American.

Available in English, Chinese Simplified, Chinese Traditional, Japanese, Korean Chinese, Vietnamese, Arabic, Bulgarian, Czech, Danish, Dutch, Farsi, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, and Turkish.

Data interface: Connect connecting Connector via RS232, RS485, and Ethernet (standard).

Information storage: 100 messages, more information can be stored via USB unlimited.

Protection: IP55 guaranteed configuration, IP65 (optional), no gas source required.



CHEEF INKJET PRINTER INK MANUFACTURER