

| | |
|--------------------------------------|---|
| Specification [Ⓟ] | Controller: 210135°37mm(HWD)/8.3°5.3°1.46inch [Ⓟ] Print head: 126 100"31mm(HWD)/4.9"3.9"1.2 inch [Ⓟ] |
| Language [Ⓟ] | Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian [Ⓟ] |
| Resolution [Ⓟ] | 50-600DPI [Ⓟ] |
| Counters [Ⓟ] | Series No, Carton No, Pallet No etc [Ⓟ] |
| Printable heights(mm) [Ⓟ] | 1-76.2mm [Ⓟ] |
| Printing speed [Ⓟ] | 0-60 m/min(300DPI) 0-30 m/min(600 DPI) [Ⓟ] |
| Production speed [Ⓟ] | Production speed can be set as request, automatic calculation and external synchronizer [Ⓟ] |
| Barcode [Ⓟ] | UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR [Ⓟ] |
| Date format [Ⓟ] | Production date, expiry date with several formats for option [Ⓟ] |
| Database support [Ⓟ] | PC software supports MS Excel, MS Access, SQL2000, SQL2005 SQL2008 etc. database formats [Ⓟ] |
| Database Source Support [Ⓟ] | Provide standard rs-232, Ethernet port, simplify the integration for customers [Ⓟ] |
| Interface [Ⓟ] | 1)7 inch 800*480 resolution color LCD touch screen [Ⓟ] 2)Display screen using new touch operation interface, easy to learn and use [Ⓟ] 3)Printer can work separately without PC software [Ⓟ] |
| Port [Ⓟ] | 1)Ethernet: 100mb/S, synchronized control of multiple devices via PC [Ⓟ] 2)USB2.0 Port: Support u-disk [Ⓟ] 3)DB15: For external devices like photocell, synchronizer or alarm kit connection [Ⓟ] |
| Ink management [Ⓟ] | Identify ink type automatically and recommend the best printing parameter [Ⓟ] Original authentic HP ink cartridge guaranteed [Ⓟ] Automatic measuring system for ink consumption [Ⓟ] |
| Installation [Ⓟ] | Standard side printing bracket, down printing bracket and anti-shock, users can install according to their needs, spring mechanism is optional [Ⓟ] |
| Power supply [Ⓟ] | AC 100v-240v 50-60hz, 90W(Specified AC adaptor) [Ⓟ] |
| Certificate [Ⓟ] | CE、FCC [Ⓟ] |