

Specification	Value
Laser Tube	CO ₂
Maximum Power	10W
Laser Cooling	Air Cooled
Maximum Print Speed	2000 characters/sec
Maximum Line Speed	900 m/min (2,940 ft/min)
Environmental Protection	IP54, 65
Beam Output	Steered Beam
Laser Source Expected Life	45,000 hours
Laser Wavelength Options	10.6 µm, 9.3 µm
Focal Distance Options	64 mm (2.50 in) – 400 mm (15.75 in)
Maximum Mark Window	485 x 351 mm (19.09 x 13.81 in)
Standard I/O Connectivity	Internal Terminal Connections
Standard User Interface	Handheld
Optional User Interface	PC, CLARiTY™ Laser Controller, TCS, Smart Graph Com
Umbilical	Detachable, 3 Lengths
Plant Air Used	No
Certifications/Approvals	CE, TÜV/NRTL, FCC Compliance (no certification required): ROHS, CDRH/FDA



2.□□□□□□□□□□□□

3.□□□□□□□□□□1□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q2□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

A□□□