



Specification	6330
Printer Mode	Intermittent and Continuous Motion
Print Gap	Consistent 0.020" (0.5mm)
Ribbon Widths	<b>6330(53mm)</b> :0.8" (20mm), 2.2" (55mm) max <b>6330(32mm)</b> :0.8" (20mm), 1.3" (33mm) max
Bar Code Printing	EAN 8, EAN 13, UPC-A, UPC-E, Code 39, EAN 128, Code 128, ITF, RSS (including 2D composite codes); others may be available upon request
Operator Interface	TFT SVGA 800x480 full-color LCD and touch screen, WYSIWYG print preview, full on-board diagnostics, 3 levels of password protection, extensive language support
Leader/Follower Capability (Up to 4 Printers Controlled by One User Interface)	Up to four Videojet DataFlex® 6330 printers controlled via a single CLARiTY™ control unit
Standard Communication	RS232, dual Ethernet, USB memory stick and scanner support, Binary and ASCII comms protocols, Windows drivers ZPL and SATO emulations
Web Browser Capability	Yes
<b>Continuous Mode:</b>	-
Maximum Print Area (Width x Length)	<b>6330(53mm)</b> :2.1" (53mm) wide x 7.9" (200mm) long <b>6330(32mm)</b> :1.3" (32mm) wide x 7.9" (200mm) long
Maximum Print Speed	29.5 in./sec (750mm/sec)
Minimum Print Speed	0.04 in./sec (1mm/sec)
Estimated Maximum Throughput (Single Line Code)	<b>6330(53mm)</b> : Up to 250 prints per minute <b>6330(32mm)</b> :Up to 250 prints per minute
<b>Intermittent Mode:</b>	-
Maximum Print Area (Width x Length)	<b>6330(53mm)</b> : 2.1" (53mm) wide x 2.95" (75mm) long <b>6330(32mm)</b> : 1.3" (32mm) wide x 2.95" (75mm) long
Maximum Print Speed	<b>6330(53mm)</b> : 29.5 in./sec (750mm/sec) <b>6330(32mm)</b> : 29.5 in./sec (750mm/sec)
Minimum Print Speed	1.6 in./sec (40mm/sec) full print quality; 0.4 in./ sec (10mm/sec) draft mode print quality

CHEEF INK PRINTER INK MANUFACTURER

