| | |
|---|---|
| Spray Head Features | plug and play; throw and change; no maintenance; stable and reliable |
| Operation Interface | with keyboard editing; computer editing with USB; remote control with ERP |
| Resolution | 300*600 DPI |
| Printing Height | 1-12.5mm (one spry head) |
| Printing Lines | 1-6 lines |
| Printing Speed | 3000 times per hour |
| Printing Fonts | built-in multiple fonts; cross bar, vertical bar, dot matrix, and entities can be free change |
| Printing Content | date, time, pictures, text, serial number, team, barcode, qr code |
| Printing Serial Number | support printing multiple serial number(each can arrive 8 numbers), skip number as scheduled |
| Printing Date | support printing date, time and time code(hour, minute, second), valid date(day, week, month, year can be chosen) |
| Printing Pictures | support complicated pictures, company logo, graphics transmission is not limited by a long-width proportional and length |
| Printing Counting | total value statistics of printing products |
| Standby Printing | automatic maintenance, preventing print head clogging |
| Printing Direction | side printing, blind printing |
| Chinese Fonts | international level one and two Chinese character library (about5000) |
| Operation Interface | picture Chinese menu (English is optional), WYSIWYG |
| Storage Function | more than 500 information |
| Ink Type | edible and eco friendly ink |
| Ink Colors | red, blue, yellow, green, etc |
| Power Supply | power adapter input AC 100-260V, 50-60hz, input DC 12v |
| Temperature Range | 10-90% non-condensing, 5-40℃ |