

|                                      |   |
|--------------------------------------|---|
| Specification <sup>↵</sup>           | Controller: 210135°37mm(HWD)/8.3°5.3°1.46inch <sup>↵</sup><br>Print head: 126 100"31mm(HWD)/4.9"3.9"1.2 inch <sup>↵</sup>   |
| Language <sup>↵</sup>                | Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian <sup>↵</sup>  |
| Resolution <sup>↵</sup>              | 50-600DPI <sup>↵</sup>  |
| Counters <sup>↵</sup>                | Series No, Carton No, Pallet No etc <sup>↵</sup>  |
| Printable heights(mm) <sup>↵</sup>   | 1-76.2mm (max 6 heads), if it is one head, the height is 12mm. <sup>↵</sup>   |
| Printing speed <sup>↵</sup>          | 0-60 m/min(300DPI) 0-30 m/min(600 DPI) <sup>↵</sup>   |
| Production speed <sup>↵</sup>        | Production speed can be set as request, automatic calculation and external synchronizer <sup>↵</sup>  |
| Barcode <sup>↵</sup>                 | UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR <sup>↵</sup>  |
| Date format <sup>↵</sup>             | Production date, expiry date with several formats for option <sup>↵</sup>   |
| Database support <sup>↵</sup>        | PC software supports MS Excel, MS Access, SQL2000, SQL2005 SQL2008 etc. database formats <sup>↵</sup>   |
| Database Source Support <sup>↵</sup> | Provide standard rs-232, Ethernet port, simplify the integration for customers <sup>↵</sup>   |
| Interface <sup>↵</sup>               | 1)7 inch 800*480 resolution color LCD touch screen <sup>↵</sup><br>2)Display screen using new touch operation interface, easy to learn and use <sup>↵</sup><br>3)Printer can work separately without PC software <sup>↵</sup>     |
| Port <sup>↵</sup>                    | 1)Ethernet: 100mb/S, synchronized control of multiple devices via PC <sup>↵</sup><br>2)USB2.0 Port: Support u-disk <sup>↵</sup><br>3)DB15: For external devices like photocell, synchronizer or alarm kit connection <sup>↵</sup> |
| Ink management <sup>↵</sup>          | Identify ink type automatically and recommend the best printing parameter <sup>↵</sup><br>Original authentic HP ink cartridge guaranteed <sup>↵</sup><br>Automatic measuring system for ink consumption <sup>↵</sup>              |
| Installation <sup>↵</sup>            | Standard side printing bracket, down printing bracket and anti-shock, users can install according to their needs, spring mechanism is optional <sup>↵</sup>   |
| Power supply <sup>↵</sup>            | AC 100v-240v 50-60hz, 90W(Specified AC adaptor) <sup>↵</sup>  |
| Certificate <sup>↵</sup>             | CE、FCC <sup>↵</sup>   |